



# TeamCard HandScan - Access



Incorporating the innovative functionality of the TeamCard B-TED system, the HandScan Access unit goes beyond function to deliver a full solution in Stadium Access Control.

The HandScan Access unit allows you to move beyond the turnstile and provide access control to areas previously hindered by structural limitations; all you need is a Wi-Fi signal and you're ready to go.

The Handscan Access unit let's you 'take the turnstile' to any area of the stadium, allowing you to accommodate your VIP, Corporate or ability challenged attendees.

Equipped with an optional Supervisor function, cardholders can be attended to without the need for a trip to the ticket office.

The TeamCard HandScan Access unit opens new doors in access control.

## Turnstile Ingress Module Features

- Online entitlement verification with TeamCard Access Control System
- Clear display and audio indicating success or fail of entitlement check
- Extended information displayed on screen when required
- Entitlement Override option with full audit and reporting

## Turnstile Supervisor Module Features

- Full card and entitlement information display including:
  - Cardholder info
  - Seat information
  - Entitlement information including status and usage details
- Option to re-enable entitlements with full audit and reporting



### Minimum Requirements

110/220v AC power outlet for unit charging  
IEEE802.11b or IEEE802.11g standard (11Mb/s-54Mb/s) Wi-Fi network

### Specifications

Unit: Samsung processor, Microsoft Windows CE, 128Mb RAM, 128Mb ROM  
 Screen: 3.5 inch QVGA ( 240x320 pixel) colour with back-light reflective TFT-LCD display, highly scratch resistance surface  
 Keyboard: 25+1 function and numeric self-luminous and back light keys  
 Speaker: Internal dual channel speaker  
 Charging: Direct connection to unit or optional charging cradle  
 Barcode Scanner: Linear 1D Laser Diode Scanning, Optical Resolution: 0.004 inch , Scan Rate: 100scans/second (bi- direction)  
 Scan Distance: 10 ~ 78mm  
 Battery: 3.7V 3200mAh Li-ion battery, which can support 8 hours continuous operation + internal backup battery  
 Weight: 400g ( including standard battery )  
 Dimensions: 190x80x25mm  
 Protective Grading: IP54, industrial sealing to prevent fine dust, rain drop and splash proof.  
 Impact Resistance: Can sustain 1.2 meters free drop on concrete  
 Operating Temperature: -15°C to 50°C  
 EMC Approved: CE & FCC



Contact us now to find out what is possible

t. 01334 476504; e. sales@scotcomms.co.uk; w. www.scotcomms.co.uk